

Model	Number of layer	Heat exchange area	DN mm	D mm	B mm	H mm	a mm	b mm	c, d mm	e, f mm	Weight Kg
P-0.63	3	2.4	695	670	190	660	65	65	32	32	270
	5	4				800					360
	7	5				930					450
	9	6				1070					540
	11	7.5				1210					630
	13	9				1350					720
	15	10				1480					810
	17	11				1740					945
	19	12				1880					1035
P-1	5	6	860	810	200	850	100	100	32	32	515
	7	8				990					650
	9	10				1130					785
	11	12				1270					920
	13	14				1410					1055
	15	16				1540					1190
	17	18				1810					1390
	19	20				1950					1525
	21	22				2080					1660
	23	24				2220					1795
	25	26				2360					1930
27	28	2630	2130								
29	30	2770	2265								
P-2	1	4	1050	860	255	650	125	125	40	40	399

2	6			720			509
3	8			810			619
4	10			890			729
5	12			960			839
6	14			1040			949
7	16			1120			1059
8	18			1200			1169
9	20			1280			1279
10	22			1360			1389
11	24			1430			1499
12	26			1510			1609
13	28			1590			1719
14	30			1670			1829
15	32			1740			1939
16	34			1970			2099
17	36			2050			2209
18	38			2130			2319
19	40			2210			2429
20	42			2290			2539
21	44			2360			2640